

2009 IECC Contractor Compliance Form

Property Information	
Property Address	
City/ZIP	
Builder / Remodeler	
Address	
Phone	

- New Construction
 Remodel Description: _____

I hereby certify that the above project will meet or exceed the minimum requirements of 2009 IECC by utilizing the following measures:

2009 IECC Zone 3 Requirements	Project Specification
Windows $U \leq 0.50$	
Windows Impact Rated $U \leq 0.65$	
Windows SHGC ≤ 0.30	
Skylight $U \leq 0.65$	
Skylight SHGC ≤ 0.30	
Doors (1 door ≤ 24 sqft exempt)	
Ceiling Insulation R-30	
Wall Insulation R-13	
Floor Insulation R-19	
Crawl space Insulation R-5 continuous / R -13 cavity	
HVAC Efficiency Rating	
HVAC sized in accordance with ACCA Manual J and Manual D	
Heat pumps have adaptive recovery thermostats	
Duct Insulation R-8 in unconditioned space, R-6 between trusses and R-0 in conditioned space	
Return from enclosed rooms must meet ACCA Manual D	
Ducts tightness per section 403.2.2 to be Verified by?	
Water Heater Efficiency Rating	
Building Envelope Air Barrier & Insulation inspection per Table 402.4.2 Verified by?	
Recessed Cans – IC air tight (ICAT)	
Pipes carrying fluids above 105 F insulated to R-3	
50% of lamps must be high efficacy	

Note: If any project specification does not meet the minimum IECC requirements, then a RESCheck or other approved simulation model must be performed and submitted with the permit application.

Signature

Date